



# TECHNISCHE MERKMALE CARATTERISTICHE TECNICHE TECHNICAL FEATURES

> Talstation Stazione a valle Lower terminal		1.015 m
> Bergstation Stazione a monte Upper terminal		1.857 m
> Geneigte Länge Lunghezza inclinata Inclined length		4.127 m
> Höhenunterschied Dislivello Vertical rise		842 m
> Fahrgeschwindigkeit Velocità massima Operation speed		6 m/sec
> Maximale Förderleistung Portata massima Transport capacity		4.000 P/h
> Tragseil Fune portante Suspension cable	Ø 67 mm - Bruchlast = 5.620 KN Ø 67 mm - Carico di rottura = 5.620 KN Ø 67 mm - Ultimate load = 5.620 KN	
> Zugseil Fune traente Pulling cable	Ø 53 mm - Bruchlast = 2.505 KN Ø 53 mm - Carico di rottura = 2.505 KN Ø 53 mm - Ultimate load = 2.505 KN	
> Antriebsleistung Potenza motore Power of drive		4 x 420 kW
> Antriebsleistung Notantrieb Potenza motore di soccorso Power of the auxiliary drive		200 kW
> Anzahl der Fahrbetriebsmittel Numero totale dei veicoli Total number of vehicles		108
> Anzahl Streckenstützen Numero sostegni in linea Total number of towers		10
> Längste Spannweite Equidistanza massima Longest segment		950 m